

# 300W-US

## Portable Power Station

US
 ZA
 EU
 FR
 UK
 AU
 JP



## Product overview

Model: SR0KW3L-SG1-US



## Product Parameters

	US	EU / UK / FR / AU / ZA	JP
<b>Battery Type</b>	Square aluminum case LiFePO <sub>4</sub> power battery		
<b>Energy Capacity</b>	204Wh		
<b>Cycle Life</b>	3000 Cycles		
<b>Depth of Discharge (DOD)</b>	95%		
<b>USB-A 1/A2 Output</b>	5V/2.4A, 12W Max.		
<b>USB-C1/C2 Output</b>	5/9/12/15V 3A, 20V/3.25A, 65W Max.		
<b>USB-C1+C2 Output</b>	5V/9V 3A, 12V/2.5A, 15V /2A, 20V/1.5A, 60W Max.		
<b>Car port Output</b>	12.6V/8A, 100W Max.		
<b>AC Output(Inverter mode)</b>	Pure sine-wave, total 300W (peak 500W), 100-120V~,60Hz, 3A *2	Pure sine-wave, total 300W (peak 500W), 220-240V~,50Hz/60Hz,1.5A	Pure sine-wave, total 300W (peak 500W), 100V~, 50Hz/60Hz, 3A*2
<b>AC Output(Bypass mode)</b>	100-120V~,60Hz, 300W Max., 3A	220-240V~,50Hz/60Hz, 300W Max., 1.5A	100-120V~, 50Hz/60Hz, 3A, 300W Max.
<b>AC input power</b>	550W Max., 6A	550W Max., 3A	6A, 550W Max.
<b>AC input voltage</b>	100-120V~, 60Hz	220-240V~, 50Hz/60Hz	100-120V~, 50Hz/60Hz
<b>Car charge input</b>	12V, DC 8A (default)		
<b>PV charge input</b>	120W Max, 12-24V, 8A		
<b>Weight</b>	≈3.65kg		
<b>Dimensions ( W*H*D )</b>	248*164*150mm		
<b>Temperature Range</b>	Discharge :-20-45°C (±3°C)		Charge: 0-45°C (±3°C)
<b>Certification</b>	 CA65,TSCA, RoHS,Reach, WEEE, POPS, UN38.3,MSDS		
Cycle Life*:Test conditions, 95% DOD, 1.0C charge & 1.0C discharge at +25±3°C.			